PE100+ QUALITY MATERIALS

Valid until October 2009

The PE100+ Association ensures the very highest quality of PE100 products by continuously monitoring three fundamental properties:

- 1) Creep Rupture Strength,
- 2) Stress Crack Resistance and
- 3) Resistance to Rapid Crack Propagation.

Network engineers have identified these to be crucial for increasing the use of PE pipes in gas and water distribution networks.

Property	Test Method	PE 100+ Association
		requirements
Creep Rupture Strength	Pressure test at 20°C	<u>> 200 h</u>
	and 12.4 MPa	
Stress Crack Resistance	Pipe notch test at 80°C	<u>> 500 h</u>
	and 9.2 bar	
Resistance to Rapid Crack Propagation	S4 Test at 0°C	p _c ≥ 10 bar

All tests are performed on 110mm - SDR 11 pipe.

On behalf of the PE100+ Association, <u>Kiwa Gastec Certification B.V.</u>, an independent testing authority in the Netherlands repeats those test rounds together with various independent and internationally respected laboratories every seven months.

Product Manufacturer BorSafe[™] HE3490-LS (black) Borealis AG BorSafe[™] HE3492-LS(orange) Borealis AG BorSafeTM HE3494-LS (blue) Borealis AG BorSafeTM HE3490-LS (black) Borouge Pte., Ltd. ELTEX® TUB 121 (black) Ineos Polyolefins ELTEX® TUB 125 N2025 (orange) Ineos Polyolefins ELTEX® TUB 124 N2025 (blue) Ineos Polyolefins ELTEX® TUB 121 N3000 (black) **Ineos Polyolefins** Hostalen CRP 100 black LyondellBasell Hostalen CRP 100 blue LyondellBasell HI-ZEX® 7700 MBK (black) Prime Polymer Co., Ltd. EVL-H®SP5505BK (black) Prime Polymer Co., Ltd. SABIC VESTOLEN® A 6060 R (black) SABIC Polyolefine GmbH SABIC VESTOLEN® A 6060 R (blue) SABIC Polyolefine GmbH SCG Chemicals & Thai Polyethylene, Ltd EL-LENE H1000PC (black) HDPE XS10H (blue) **Total Petrochemicals** HDPE XS10B (black) **Total Petrochemicals** HDPE XS10 Orange YCF **Total Petrochemicals**

The following products met the PE 100+ requirements

For further information please contact: